

Door Range

Insulated Sliding Door Cold Room Type E





Insulated Sliding Cold Room Door Type E

Description and Application

The Isocab insulated sliding cold room door is designed for high cycle applications. The door come in either manual or motor operated systems. All door components including track, panel gasket system are designed to provide years of trouble free service.

The door is for both cooler and freezer applications.

Finishes

The door leaf is delivered in standard coated galvanized steel (CLEAN *safe* 25).

Other finishes are also available (i.e. stainless steel). Please contact your Sales Manager for more information.

Specifications

The sliding cold room door is easy to install and maintain and meets the high requirements and specifications of the food processing industry.



Technical data

Applications	Small to mid-size chill cold rooms / Freezer rooms
Door leaf	 60mm (pos. temp.) injected PU foam (CFC-free) 100mm (neg. temp.) injected PU foam (CFC-free) 300 x 600mm
Finishes	 Standard: coated galvanized steel (CLEANsafe 25) RAL 9002 (other colours on request) CLEANsafe 55 RAL 9002, 9010 Stainless steel (304, 316L)
Dimensions	 Min. 800 x 1900mm Max. 2030 x 3030mm Special sizes on request
Door Frame	Standard ALU RAL 9002, 9010, anodized PVC RAL 9002 Stainless steel or coated steel encasing the frame
Fittings	Anodized aluminium rail system
Options	 Rail access port Swanneck (metalized - stainless steel) Anodized aluminium wall guide sliding system (positive temperature only) Automatic operation (Type L - door) Safety lock





Your distributor

Care has been taken to ensure that the contents of this publication are accurate, but Isocab does not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use or application of products or methods of working are for information only and Isocab accepts no liability in respect thereof.



DRTF-04.2014-EN

Isocab nv • Treurnietstraat 10 • B-8531 Bavikhove • T +32 [0] 56 73 43 11 • F +32 [0] 56 73 43 22 • info@isocab.be • www.isocab.com

Isocab France sas • Z.I. de Grande Synthe • 3 Rue Charles Fourier • CS 30142 • F-59792 Grande Synthe CEDEX • T +33 [0] 3 28 29 24 40 • F +33 [0] 3 28 29 24 50 • info@isocabfrance.fr