


KS 600 / 900 /1000 EB

Panel Dimensions

Euro Box Profile



Available Panel Thicknesses
80
100
120
140
150

Note for KS1000 WV Profile: 9x6mm PVC foam tape should be used instead of the noted 4mm diameter butyl rubber sealant between the face of the panel and any external flashings including vertical tophat flashings.

Notes:

Rev	Description	Chkd	Date



**Insulated Roof  
& Wall Panels**

**enviro<sup>care</sup>**

**TECHNICAL SERVICES**

**Kingspan Limited**  
Greenfield Business Park No. 2, Greenfield,  
Holywell, Flintshire, CH8 7GJ, UK  
[www.kingspanpanels.co.uk](http://www.kingspanpanels.co.uk)  
t: 0800 587 0090

Carrickmacross Road,  
Kingscourt, Co.Cavan, Ireland  
[www.kingspanpanels.ie](http://www.kingspanpanels.ie)  
t: 00353 42 96 98529

Client

Project

Drawing

**KS1000 AWP  
EB Profile Drawing**

Status

Drawn by RL	Checked by JP	Date 11/02/15
----------------	------------------	------------------

Drawing Number AWPHz15004	Revision
------------------------------	----------

*This drawing is the property of Kingspan and  
may not be reproduced in any way without  
written consent from Kingspan.*