


KS1000 AWP / LPCB insulated wall panel horizontally laid

Self-drilling self-tapping primary fixings with minimum 16mm diameter non-ferrous EPDM backed washer

AWP joint filler bedded on gun grade sealant

Kingspan Multibeam



Notes:

Rev	Description	Chkd	Date



Insulated Roof  
& Wall Panels

**enviro***care*<sup>®</sup>

TECHNICAL SERVICES

**Kingspan Limited**  
Greenfield Business Park No. 2, Greenfield,  
Holywell, Flintshire, CH8 7GJ, UK  
www.kingspanpanels.co.uk  
t: 0800 587 0090

Carrickmacross Road,  
Kingscourt, Co.Cavan, Ireland  
www.kingspanpanels.ie  
t: 00353 42 96 98529

Client

Project

Drawing

KS1000 AWP Hz  
Hz Joint Fix Locations

Status

Drawn by	Checked by	Date
RL	JP	11/02/15

Drawing Number	Revision
AWPHz15009	

*This drawing is the property of Kingspan and may not be reproduced in any way without written consent from Kingspan.*

Note for KS1000WV Profile: 9x6mm PVC foam tape should be used instead of the noted 4mm diameter butyl rubber sealant between the face of the panel and any external flashings including vertical tophat flashings.