



Low profile self-drilling self-tapping primary fixings at 1000mm centres

Air seal - EPDM VJ2 bubble gasket 95x10mm

Curved horizontal steelwork

KS1000 AWP / LPCB insulated wall panel vertically laid pre-formed corner unit

Self-drilling self-tapping primary fixings with minimum 16mm diameter non-ferrous EPDM backed washer

KS1000 AWP / LPCB certified insulated wall panel horizontally laid
Air seal gun grade seal to male joint inline with internal air seal
Vertical tophat and insert

Note for KS1000WV Profile: 9x6mm PVC foam tape should be used instead of the noted 4mm diameter butyl rubber sealant between the face of the panel and any external flashings including vertical tophat flashings.

Notes:

Rev	Description	Chkd	Date



Insulated Roof & Wall Panels

envirocare[®]

TECHNICAL SERVICES

Kingspan Limited
Greenfield Business Park No. 2, Greenfield,
Holywell, Flintshire, CH8 7GJ, UK
www.kingspanpanels.co.uk
t: 0800 587 0090

Carrickmacross Road,
Kingscourt, Co.Cavan, Ireland
www.kingspanpanels.ie
t: 00353 42 96 98529

Client

Project

Drawing

KS1000 AWP Hz
Curved corner

Status

Drawn by RL	Checked by JP	Date 15/03/15
Drawing Number AWP Vrt15018		Revision

This drawing is the property of Kingspan and may not be reproduced in any way without written consent from Kingspan.