


KS 600 / 900 /1000 FL-S

Panel Dimensions

Flat - Flat Stucco



| Available Panel Thicknesses |
|-----------------------------|
| 45                          |
| 60                          |
| 70                          |
| 80                          |
| 100                         |
| 120                         |
| 140                         |
| 150                         |

Note for KS1000 WV Profile: 9x6mm PVC foam tape should be used instead of the noted 4mm diameter butyl rubber sealant between the face of the panel and any external flashings including vertical tophat flashings.

Notes:

| Rev | Description | Chkd | Date |
|-----|-------------|------|------|
|     |             |      |      |



Insulated Roof  
& Wall Panels

**enviro***care*

TECHNICAL SERVICES

**Kingspan Limited**  
Greenfield Business Park No. 2, Greenfield,  
Holywell, Flintshire, CH8 7GJ, UK  
www.kingspanpanels.co.uk  
t: 0800 587 0090

Carrickmacross Road,  
Kingscourt, Co.Cavan, Ireland  
www.kingspanpanels.ie  
t: 00353 42 96 98529

Client

Project

Drawing

KS1000 AWP  
FL Profile Drawing

Status

|                |                  |                  |
|----------------|------------------|------------------|
| Drawn by<br>RL | Checked by<br>JP | Date<br>11/02/15 |
|----------------|------------------|------------------|

|                              |          |
|------------------------------|----------|
| Drawing Number<br>AWPHz15003 | Revision |
|------------------------------|----------|

*This drawing is the property of Kingspan and may not be reproduced in any way without written consent from Kingspan.*