

Kingspan Multibeam

KS1000 Optimo / LPCB insulated wall panel horizontally laid

Self-drilling self-tapping primary fixings with minimum 16mm diameter non-ferrous EPDM backed washer

Internal cleader angle with 100mm overlap sealed with film backed butyl tape or gun grade sealant

Air seal gun grade seal to male joint inline with internal air seal


Site applied fire rated canister insualtion

Air seal - 6mm bead gun grade sealant

External corner flashing with 100mm sealed overlaps or butt strap

4mm diameter butyl rubber sealant

Low profile stitching screws with minimum 14mm diameter non-ferrous EPDM backed washer fitted at maximum 450mm centres



Notes:

Rev	Description	Chkd	Date
-----	-------------	------	------



Insulated Roof & Wall Panels



Kingspan Limited
Greenfield Business Park No. 2, Greenfield,
Holywell, Flintshire, CH8 7GJ, UK
www.kingspanpanels.co.uk
t: 0800 587 0090

Carrickmacross Road,
Kingscourt, Co.Cavan, Ireland
www.kingspanpanels.ie
t: 00353 42 96 98529

Client

Project

Drawing

KS1000 Optimo Hz
External Flashed Corner

Status

Drawn by RL	Checked by JP	Date 12/12/15
----------------	------------------	------------------

Drawing Number OptimoHz15009	Revision
---------------------------------	----------

This drawing is the property of Kingspan and may not be reproduced in any way without written consent from Kingspan.