

Self-drilling self-tapping primary fixings with minimum 16mm diameter non-ferrous EPDM backed washer

4mm Diameter butyl rubber sealant

Site applied LPCB certified insulation board

Option A vertical tophat and insert


Air seal gun grade seal to male joint inline with internal air seal

AWP joint filler bedded on gun grade sealant

EPDM VJ2 bubble gasket

Kingspan Multibeam

KS1000 Optimo / LPCB insulated wall panel horizontally laid pre-formed corner unit



Self-drilling self-tapping primary fixings with minimum 16mm diameter non-ferrous EPDM backed washer

AWP joint filler bedded on gun grade sealant

KS1000 Optimo / LPCB certified insulated wall panel horizontally laid

Air seal gun grade seal to male joint inline with internal air seal

Option A vertical tophat and insert

Pre-formed panels maximum un-supported length is 1000mm, for longer panels additional steel work is required.

Notes:

Rev	Description	Chkd	Date



Insulated Roof & Wall Panels



Kingspan Limited
Greenfield Business Park No. 2, Greenfield,
Holywell, Flintshire, CH8 7GJ, UK
www.kingspanpanels.co.uk
t: 0800 587 0090

Carrickmacross Road,
Kingscourt, Co.Cavan, Ireland
www.kingspanpanels.ie
t: 00353 42 96 98529

Client

Project

Drawing
**KS1000 Optimo Hz
External Cranked Corner**

Status

Drawn by RL	Checked by JP	Date 12/12/15
----------------	------------------	------------------

Drawing Number OptimoHz15007	Revision
---------------------------------	----------

This drawing is the property of Kingspan and may not be reproduced in any way without written consent from Kingspan.