


- KS1000 Optimo / LPCB insulated wall panel horizontally laid
- Internal closure flashing with 100mm overlap
- Site applied LPCB certified PIR insulation board any gaps filled with fire rated canister insulation
- Low profile stitching screws with minimum 14mm diameter non ferrous EPDM backed washer fitted at maximum 450mm centres
- Air seal - 6mm bead of gun grade sealant
- Self-drilling self-tapping primary fixings with minimum 19mm diameter non-ferrous EPDM backed washer at 1000mm centres
- Drip flashing with 100mm sealed overlaps or butt straps
- External closure flashing with 100mm sealed overlaps or butt straps
- Kingspan Multibeam any joints sealed with a film backed butyl tape
- Soffit flashing with 100mm sealed butt straps
- Door track



Notes:

Rev	Description	Chkd	Date



Insulated Roof  
& Wall Panels



**Kingspan Limited**  
Greenfield Business Park No. 2, Greenfield,  
Holywell, Flintshire, CH8 7GJ, UK  
www.kingspanpanels.co.uk  
t: 0800 587 0090

Carrickmacross Road,  
Kingscourt, Co.Cavan, Ireland  
www.kingspanpanels.ie  
t: 00353 42 96 98529

Client

Project

Drawing

KS1000 Optimo Hz  
Roller Shutter Door Head

Status

Drawn by	Checked by	Date
RL	JP	12/12/15

Drawing Number	Revision
OptimoHz15034	

*This drawing is the property of Kingspan and  
may not be reproduced in any way without  
written consent from Kingspan.*